



designed for scientists



MS 3 basic

/// Data Sheet

Compact, universal small shaker suitable for shaking tasks with all small vessels and microtiter plates

- Wide range of attachments
- Attachment detection
- Continuous or touch operation (with standard attachment)
- Two operating modes:
Mode A (safe mode with attachment detection)
the maximum speed of 3.000 rpm is only reached with the standard attachment in



designed for scientists

touch mode. When using other attachments the speed is limited to 1.300 rpm.

Mode B (without attachment detection)

a speed of 3000 rpm is possible with all attachments, depending on the application (see the speed range of the accessory list)

- Stable in all speed ranges
- Sturdy zinc die cast casing



designed for scientists

Technical Data

| | |
|--|----------------------|
| Type of movement | orbital |
| Shaker diameter [mm] | 4.5 |
| Permissible shaking weight (incl. attachment) [kg] | 0.5 |
| Motor rating input [W] | 10 |
| Motor rating output [W] | 8 |
| Permissible ON time [%] | 100 |
| Speed min (adjustable) [rpm] | 200 |
| Speed range [rpm] | 0 - 3000 |
| Speed display | scale |
| Operating mode | continuous operation |
| Touch function | yes |
| Working with microtiter plates | yes |
| Number of microtiter plates | 1 |
| Dimensions (W x H x D) [mm] | 148 x 63 x 205 |
| Weight [kg] | 2.9 |
| Permissible ambient temperature [°C] | 5 - 40 |
| Permissible relative humidity [%] | 80 |
| Protection class according to DIN EN 60529 | IP 21 |
| Voltage [V] | 100 - 240 |
| Frequency [Hz] | 50/60 |
| Power input [W] | 20 |
| DC Voltage [V=] | 24 |
| Current consumption [mA] | 800 |